

# PLASTIC-RUBBER COMPOSITE WHEEL STOP











# Advantages +



## **PLASTIC-RUBBER COMPOSITE**

Cost effective, UV-resistant, and very sturdy.



## **HEAVY-DUTY STRUCTURE**

Thick walls and V-shaped ribs for maximum strength in tough conditions.



#### **REFLECTIVE FILMS**

Embedded thermoplastic reflective road marking films to enhance visibility and safety.





#### **CONVENIENT STORAGE**

Screws, anchors, and caps stored underneath for easy setup.



#### **CUSTOM-MADE PACKING**

Designed for international shipping, easy storage and delivery.

PRODUCTS	TYPES	OVERALL DIMENSIONS (L*W*H)	MOUNTING HARDWARE
	550 mm (2')	550 x 150 x 100 mm (2' x 6" x 4")	Coach screw: M12 x 160 mm (M12 x 6")  Anchor: Ø 17 x 105 mm (Ø 0.67" x 4.1")  Cap: Ø 33.5 mm (Ø 1.32")
	900 mm (3')	900x 150 x 100 mm (3' x 6" x 4")	
	1220 mm (4')	1220 x 150 x 100 mm (4' x 6" x 4")	
	1830 mm (6')	1830 x 150 x 100 mm (6' x 6" x 4")	

# **BEST SELLERS**











